

FOOD GRADE SILICONE GASKET



SOFTENING RESIN



FOOD GRADE MATERIAL

Filter Cartridge MODEL NUMBER. UDFR

Installation Instructions

After installing this new cartridge pass 5 galon of top water through to flush out any resin fine particle presentin the unit.

Ar bubbles may be present for the first few days wher installation.

To Keep your filter system operating efficiently. replace this cartridge annualty or by the recommendation of your experienced water conditions dealer.

SERVICE LIFE 2500 GAL

10 INCH SOFTENING RESIN FILTER ELEMENT

- Softened water
- Remove scale
- Minerals
- floating object

Filter Cartridge MODEL NUMBER. UDFR Installation Instructions After installing this new cartridge pass 5 palus of top water through to flush out any resin fine Differensentin the unit. Ar bubbles may be present for the first few sign of or installation. To Keep your filter system operating efficiently implace this cartridge annually or by the reconhendston of your experienced water conditions SERVICE LIFE 2500 GAL

SOFTENED RESIN FILTER

The softening resin adopts imported softening resin. Through the interaction of the cations in the resin and the carbonate ions in the water, the calcium and magnesium ions in the water are converted to reduce the hardness of the water and reduce the scale.

Filter Cartridge MODEL NUMBER

UDFR

Installation Instructions

After installing this new cartridge pass 5 palor of tro water through so flush out any resin fire perficie researcing the unit.

Ar buttles may be present for the first few days

To Keep your filter system operating efficiently trolace this cartridge annually or by the recontrendation of your experienced water conditions finder.

SERVICE LIFE 2500 GAL

PRODUCT PARAMETERS



Product Name : Softened resin filter Product Size : 250*60mm

Product Material: Cation exchange resin Maximum Temperature: 4-45C°

Applicable Water Quality: Municipal tap water
Exchange Capacity: 4.7mm01/g